



CATALOG NUMBER	TYPE
PROJECT NAME	DATE

SPECIFICATIONS

FEATURES

- Edge-lit exit sign with extruded aluminum trim
- Slim-profile design complements upscale commercial or retail applications
- Can be ordered with special wording face panel
- Designed for wall or ceiling recessed mounting

CONSTRUCTION

- Aluminum housing and acrylic panel
- Available with 6", 8", or 10" EXIT letter height
- Field-selectable chevron directional indicator offers a choice of direction on-site

ELECTRONICS

- Dual-voltage input capability: 120/277V
- Low-voltage disconnect
- AC indicator light with test switch
- Brownout protection

LAMP

- AlGalnP L.E.D. with a rated life of 10+ years

BATTERY

- EM option comes standard with nickel-cadmium battery
- Provides a minimum of 90 minutes upon loss of power
- Operating temperature range: 10-40° C

COMPLIANCE

- Meets or exceeds UL 924, NFPA 101, NEC and OSHA illumination standards

WARRANTY



- 5-year warranty on housing and electronics. Battery is prorated

ELX-UNVRC

RECESSED L.E.D. EDGE-LIT EXIT SIGN



DIMENSIONS



Material	Mounting	Battery	Code Compliance
Aluminum	Wall / Ceiling	Nickel-cadmium	UL 924

ORDERING GUIDE

MODEL	LETTER HEIGHT	NO. OF FACES	LETTER/BACKGROUND	TRIM EXTRUSION FINISH	POWER CONFIGURATION	OPTIONS
ELX-UNVRC Recessed LED Edgelit Sign	6 6" Letters 8 8" Letters 10 10" Letters	1 Single 2 Double UNV Universal	RC ¹ Red on Clear RW Red on White RM Red on Mirrored RB Red on Black GC ¹ Green on Clear GW Green on White GM Green on Mirrored GB Green on Black	BA Brushed Aluminum WHT White BLK Black DB Dark Bronze BR Brass	AC AC Only EM Battery Backup DI Dual Input Transformer	SD Self Diagnostics SW Special Wording CAD Caddy Bars 220 220 VAC 60Hz

Notes:

1. Single face only