

CATALOG NUMBER	TYPE
PROJECT NAME	DATE

# **SPECIFICATIONS**

## **FEATURES**

- Steel exit sign designed for use in New York City
- Designed for wall mounting

#### CONSTRUCTION

- Steel construction with matte white or blackpowder coating
- Field-selectable chevron directional indicator offers a choice of direction on-site
- The face design features 8" letters with 1" stroke; 100ft viewing distance

## **ELECTRONICS**

- Dual-voltage input capability: 120/277V
- Low-voltage disconnect
- · AC indicator light with test switch
- Brownout protection

#### LAMP

• AllnGaP LEDs with a rated life of 10+ years

#### **BATTERY**

- Nickel-cadmium battery is standard and provides a minimum of 90 minutes of illumination in emergency mode
- Operating temperature range: 10-40° C

#### **COMPLIANCE**

- Suitable for damp or wet applications
- Meets or exceeds UL 924, NFPA 101, NEC and OSHA illumination standards

## WARRANTY

3-year warranty on housing and electronics. Battery is prorated


# **WEANY**

NYC STEEL EXIT SIGN FOR WET LOCATION





# **DIMENSIONS**





Material	Mounting	Battery	Code Compliance	Dimensions
Steel	Wall	Nickel-cadmium	UL 924	14.4" W X 10.2" H X 2.1" D

# **ORDERING GUIDE**



ASTRALITE, INC. 20 POCONO ROAD BROOKFIELD CT 06804 203.775.0172 (P) CS@ASTRALITELIGHTING.COM WWW.ASTRALITELIGHTING.COM